



Tubex Easywrap

Description Extruded polypropylene coiled tube which protects and helps establish trees.

Application For the protection of trees against animal browsing and herbicide spray.

Sectors Forestry and Horticulture.

Twin wall; best strength to 'weight ratio'.

UV Stabilised: provides minimum 5 year protection.



Overlap; expands as tree grows.

Translucent green; maximises light transmission for photosynthesis.

		TUBEX Easywrap		
Dimensions				
Height	m	0.2	0.6	0.75
Diameter	mm	50	50	50
Overlap Tolerance	mm	32 (min) - 50 (max)	32 (min) - 50 (max)	32 (min) - 50 (max)
Av. Weight per Tube	g	21.5	43.5	54
Packaging		For all sizes		
Nest		2	2	2
Bundle		100	150	150
Bag or Strap Banded		Bag	Bag	Bag

Material	For All Sizes
Tube	Polypropylene
Colour	Green
Service Life	Minimum 3 Years
Degradability	Photodegradable
Manufacturing Tolerance	- 10mm
Recommended Support	Cane

Green-tech endeavour to ensure that the information given on this technical data sheet is accurate, but accept no liability for its use or its suitability for particular application.

Rabbit Hill Business Park, Great North Road, Arkendale, Knaresborough HG5 0FF

T: 01423 332100 E: sales@green-tech.co.uk W: www.green-tech.co.uk Facebook: @greentechuk Twitter: @greentechltd

