

Tubex Ecostart

Description Extruded polypropylene tube which protects and helps establish trees.

Application For the protection of trees against animal browsing, herbicide spray and for the improvement of

growth through a microclimate.

Sectors Forestry and Horticulture.

Strengthening rods; prevents shelter tearing at stake area.

Twin wall; best strength to weight ratio.

UV Stabilised: provides miniumum 5 year protection.


Flared rim; minimises stem abrasion.

Laserline; shelter splits avoiding strangulation as tree grows.

Pre-fitted releasable ties; quick, easy installation and maintenance.

Translucent green; maximises light transmission for photosynthesis.

		Ecostart		
Dimensions				
Height	m	0.6	0.75	
Diameter	mm	57 - 73	57 - 73	
No. of Ties		1	2	
Type of Tie		Releasable	Releasable	
Size of Tie	inch	8	8	
Top Tie Height		225 265	405 515	
(+tolerance)	mm	335 - 365	485 - 515	
Bottom Tie Height			105 215	
(+tolerance)	mm	-	185 - 215	
Av. Weight per Tube	g	45	55.5	
Packaging		For Al	For All Sizes	
Nest		3	3	
Bundle		150	150	
Bag or Strap Banded		Bag	Bag	





Material	For All Sizes
Tube	Polypropylene
Tie	Nylon
Colour	Green
Service Life	Minimum 3 Years
Degradability	Photodegradable
Manufacturing Tolerance	-2.5cm
Recommended Support	Stake