



# Shelterguard and Treeguard Installation

## Shelterguard and Treeguard for trees

It is recommended that the supporting stake is at least 15cm taller than the height of the guard to ensure that support is provided high enough up the guard after the stake has been hammered into the ground.

1. Carefully plant the tree.
2. Knock in the stake - close to the tree but not so close as to damage roots. Make sure to keep the stake vertical, especially when planting on slopes.
3. When protecting 'feathered' trees be sure to gather branches before sliding guard over the tree.
4. Carefully slide guard over tree.
5. Ensure that ties go over the stake at the same time as the guard is fitted over the tree.
6. Firm the guard approximately 1-2cm into the ground to provide a safe seal from herbicides (when using shelterguard) and to deter animals from trying to burrow under the guard.
7. Tighten ratchet ties and tuck in the loose ends. Not only does this look neater but it also deters deer/sheep from nibbling the ends of the ties.



Green-tech endeavour to ensure that the information given on this technical data sheet is accurate, but accept no liability for its use or its suitability for particular application.

Rabbit Hill Business Park, Great North Road, Arkendale, Knaresborough HG5 0FF

T: 01423 332100 E: sales@green-tech.co.uk W: www.green-tech.co.uk Facebook: @greentechuk Twitter: @greentechltd