

## Bodpave 40 - Gravel Surfaces

### Installation Guide

1. Place paver units with spikes downwards onto the prepared sub-base + bedding layer. Edging boards or kerbs are recommended, to aid gravel retention.
2. Connect the pavers using the ground spikes and loops, progressing over the area in rows. Use protective gloves to avoid abrasions.
3. Pavers can be cut using a hand or power saw to fit around obstructions and curves. Cut pieces which are less than half the original size should be avoided where possible.
4. Fill the pavers to the top of the cells with the specified angular decorative aggregate. If required, use a light vibrating plate to consolidate the aggregate into the cells. Top up cells with aggregate as necessary. Fully rounded 'pea gravel' is not recommended.
5. If the area is to be used as horse paddock, it is preferable to cover the area with a 50-100mm thick layer of fine sand/mulch.
6. The surface may be trafficked immediately.

### Notes

**Note 1:** If the TX160 geogrid layer is omitted, then the total sub-base layer thickness (T) must be increased by 50%.

**Note 2:** A'DoT Type 1' sub-base may be used, provided that an adequate drainage system is installed (refer to note 4). Alternatively a porous/open-graded (reduced fines) sub-base layer may be specified, e.g as part of a Sustainable Urban Drainage System (SUDS) application. If a 'reduced fines' sub-base layer is specified, this must be covered with either a geotextile filter membrane and/or a suitable clean gravel blinding layer, to avoid fine particles entering the sub-base layer. Do not use sand for the paver bedding layer.



**Note 3:** Specific advice on ground conditions, CBR% and construction over ground with a CBR less than 1% is available from Boddingtons. CBR% = California Bearing Ratio, a measurement of subgrade soil strength.

**Note 4:** Typical drainage details; 100mm diameter perforated pipe drain laid at minimum gradient 1:100, bedded on gravel in trench backfilled with 'DoT Type A' drainage aggregate, covered or wrapped with a BGT100 geotextile fabric and leading to a suitable outfall or soakaway. Drains placed down centre or one edge of access routes up to 5m wide.

Flexible Lining Products is a trading style of Greentech Ltd.

Rabbit Hill Business Park, Great North Road, Arkendale, Knaresborough HG5 0FF

UK. Tel: +44 (0)1423 332100

Fax: +44 (0)1423 332101

Email: sales@green-tech.co.uk

Web: www.green-tech.co.uk

## Bodpave 40 - Grass Surfaces

Wider areas may require additional drains at 5m - 10m centres. Drainage design to be determined by the specifier based on specific conditions on site.

**Note 5:** Maximum advised gradient for traffic applications is 12% (1:8) 7°. Pegging may be required.

**Note 6:** BodPave®40 complies with BS8300:2001 - "Design of buildings and their approaches to meet the needs of disabled people" - Code of Practice. (ISBN 0580384381)

### Typical Sub-base Thickness Requirements

Application/Load	CBR (%) Strength of Subgrade Soil	(T) DoT Sub-base Thickness (mm)	Geogrid
<b>Fire truck and occasional HGV access</b>	≥ 6	100	TX160
	= 4 < 6	120	TX160
	= 2 < 4	190	TX160
	= 1 < 2	380	TX160
<b>Light vehicle access and overspill car parking</b>	≥ 6	100	TX160
	= 4 < 6	100	TX160
	= 2 < 4	135	TX160
	= 1 < 2	260	TX160

Flexible Lining Products is a trading style of Greentech Ltd.

Rabbit Hill Business Park, Great North Road, Arkendale, Knaresborough HG5 0FF

UK. Tel: +44 (0)1423 332100

Fax: +44 (0)1423 332101

Email: sales@green-tech.co.uk

Web: www.green-tech.co.uk

FLP endeavour to ensure that the information given on this technical data sheets is accurate, but accept no liability for its use or suitability for particular application.

## Paving Grid Specification

Description	Data
Product Material Colour Paver Dimensions Paver Size Laid Nominal Cell Size Cell Wall Thickness Weight Load Bearing Capacity Central Base Support Open Cell % Connection Type Chemical Resistance UV Resistance Toxicity	BodPave®40 Rigid 100% recycled polyethylene Green 500mm x 500mm x 40mm 500mm x 500mm (4 grids per m2) 60mm Octagonal 2.7mm - 3.2mm 1.2kg/paver - (4.80kg/m2) 150 tonnes/m2 (Crush resistance) 25mm long pegs on underside (4 per paver) Top 95% / Base 75% Spike and loop edge connection Excellent High Non Toxic
Bedding Layer	60:40 rootzone : 50-70mm thick
Paver Fill (seed bed)	60:40 rootzone : 33-35mm thick
Grass seed or turf	35g/m2 amenity blend low maintenance seed or turf as required.
Fertiliser	Pre-seed fertiliser followed up with appropriate seasonal fertiliser.
Sub-base type	DoT Type 3 or a modified porous sub-base. DoT Type 1 with drains
Sub-base reinforcement	TX160 Triaxial Geogrid

Flexible Lining Products is a trading style of Greentech Ltd.  
 Rabbit Hill Business Park, Great North Road, Arkendale, Knaresborough HG5 0FF  
 UK. Tel: +44 (0)1423 332100 Fax: +44 (0)1423 332101  
 Email: sales@green-tech.co.uk Web: www.green-tech.co.uk

FLP endeavour to ensure that the information given on this technical data sheets is accurate, but accept no liability for its use or suitability for particular application.

### Field Guidance for Estimating Sub-Grade Strengths

Consistency	Indicator			Strength	
	Tactile (feel)	Visual (observation)	Mechanical (test)	CBR	CU
			SPT	%	kN/sqm
Very Soft	Hand sample squeezes through fingers	Man standing will sink >75mm	<2	<1	<25
Soft	Easily moulded by finger pressure	Man walking sinks 50-75mm	2-4	Around 1	Around 25
Medium	Moulded by moderate finger pressure	Man walking sinks 25mm	4-8	1-2	25-40
Firm	Moulded by strong finger pressure	Utility truck ruts 10-25mm	8-15	2-4	40-75
Stiff	Cannot be moulded but can be indented by thumb	Loaded construction vehicle ruts by 25mm	15-30	4-6	75-150

**Flexible Lining Products is a trading style of Greentech Ltd.**  
**Rabbit Hill Business Park, Great North Road, Arkendale, Knaresborough HG5 0FF**  
**UK. Tel:** +44 (0)1423 332100      **Fax:** +44 (0)1423 332101  
**Email:** sales@green-tech.co.uk      **Web:** www.green-tech.co.uk

FLP endeavour to ensure that the information given on this technical data sheets is accurate, but accept no liability for its use or suitability for particular application.