Technical Data Sheet

TREEPARKER SANDWICHPANEL 52/74



Urban Tree Planting & Tree Irrigation

Horizontal/vertical load-bearing and spreading drainage system

Material: Recycled polypropyleen (PP)

Colour: Black/anthracite


Weight: 4,49 kg per m²

Dimensions: 1040 mm (l) x 960 mm (w) x 52 mm (h)

 $1 \text{ m} \approx 8 \text{ units}$

Life expectancy: 50 years

HS code: 39269097



Top view 1 unit

_			4	20 n	nm					
		I'~'				<u>"~"</u>			-	1
$\overline{\bigcirc}$		\mathbb{R}^{2}	$\frac{1}{2}$	\subseteq	$\frac{2}{6}$	$\frac{1}{2}$	$\frac{9}{2}$	\subseteq	į	
\mathcal{Q}	\Box	$\frac{\circ}{\circ}$	$\overline{\Omega}$	$\overline{\bigcirc}$	$\overline{\mathbb{Q}}$	\bigcirc	$\overline{\mathcal{O}}$	0		26C
10	\bigcirc	\bigcirc	\bigcirc	Ω	\bigcirc	\bigcirc	\bigcirc	0		0 mm
0	\bigcirc	0	\bigcirc	0	\bigcirc	0	\bigcirc	0		3
\circ	0	0	0	0	0	0	0	0		

Detail: integrated connectors

Functional Specifications

Pressure resistance

• 74 t/m (ASTM D1621) taxable directly on the panel

Drainage

• Infiltration rate: 189 l/min/m

• Threedimensional flowable/rootable

Connections

- Integrated conical coupling system
- Equipped with a click system on all sides to create large one piece surfaces

Custom-made

• Panels can easily be tailored without loss of compressive strength



